

400NK

CHASSIS

SUSPENSION	Front: retractable type Rear: cantilever type
BRAKE	Hydraulic
RIM	Front: 3.5 x 17 MT Rear: 4.5 x 17 MT
TIRE	Front: 120 / 70 ZR17 Rear: 180 / 60 ZR17
COLOR	Pearl White, Athens Blue

ENGINE

ENGINE TYPE	2-cylinder inline, 8-valve, Liquid cooled, DOHC, BOSCH EFI
DISPLACEMENT	400.4 cc
BORE X STROKE	68.4 x 54.5 mm
MAXIMUM POWER	30.5 kW / 9500 rpm
MAXIMUM TORQUE	14.4 N.m / 7650 rpm
COMPRESSION RATIO	11.1:1
FUEL SUPPLY	EFI
IGNITION	ECU
SPEEDING WAY	6-speed

VEHICLE

LENGTH X WIDTH X HEIGHT	2114 x 757 x 1100 mm
WHEELBASE	1415 mm
SEAT HEIGHT	815 mm
MINIMUM GROUND CLEARANCE	150 mm
MINIMUM TURNING DIAMETER	5.4 m
CURB WEIGHT	206 kg
MAXIMUM PAYLOAD CAPACITY	150 kg
FUEL CAPACITY	17 L
MAXIMUM SPEED	155 km/h



Pearl White



Athens Blue

Authorized dealer

© 2017, ZHEJIANG CFMOTO POWER CO., LTD.

This product form covers all contents, the parameters are for reference only, because the technical change is not in accordance with the real vehicle, please take the actual vehicle as the standard. Zhejiang CFMOTO power shares have the account. The division reserves the right of interpretation. For more information, please visit <http://www.cfmoto.com> Design in August 2017



ZHEJIANG CFMOTO POWER CO., LTD.

No. 116, Wuzhou Road, Yuhang Economic Development Zone
Hangzhou 311100, Zhejiang
ProvinceTel: 86-571-89265799 Fax: 86-571-89265788
Email: export@cfmoto.com, www.cfmoto.cn



400NK

DESIGN

Our engineers put an unbelievable amount of thought into the development of this street bike, clearly it was well thought out as it has a compact body design with sleek, simple lines contributing to its sporty appearance.

EXCELLENT CORNERING

There's no doubt about the fact that cornering stability is essential. Thankfully, the 400NK inherited the easy handling of the rest of the NK family which allows for fast, sharp control in every bend.



ENGINE

The powerful 400.4 cc engine has slide bearing technology for higher engine reliability. Hydraulic tensioner technology reduces engine noise and the BOSCH EFI system with a dual 38 mm throttle contributes to lower emissions.

HYDRAULIC TENSIONER

Aids in adding more stability while reducing engine noise.



GO EMBRACE NEW POSSIBILITIES
BEYOND



BRAKE SYSTEM/ABS

The optional continental ABS system provides unrivaled stopping-ability to the 400NK for shorter braking distances and more braking power. Fitted with floating double 300 mm brakes and dual piston calipers at the front, with a single 220 mm brake disk and single piston caliper up rear.



LCD DASHBOARD

LCD dashboard with backlights allows for easy readability of various functions on the bike while on the move.